

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
002 981 1305	55.000	90.000	23.000			
008 981 2805	40.000	90.975	32.000			
011 981 1305	75.000	140.000	34.210			
012 981 9205	60.000	130.000	34.000			
012 981 9305	60.000	137.300	33.700			
02476/02420	31.750	68.263	22.225	0.381	51.155	42.036
02872/02820	28.575	73.025	22.225	0.465	99.000	140.000
02878/02820	34.925	73.025	22.225	0.421	78.800	74.900
03062/03162	15.875	41.275	14.288	0.090	25.500	21.200
07079/07196	20.000	50.005	13.495	0.135	23.131	17.126
07093/07196	23.813	50.005	13.495	0.120	27.000	29.600
07098/07196	24.981	50.005	13.495	0.115	27.000	29.600
07100 S/07210 X	25.400	50.800	15.011	0.129	32.000	30.500
09067/09195	19.050	49.225	18.034	0.170	39.100	40.000
09074/09195VQ494	19.050	49.225	19.845	0.180		
104947/104911	50.000	82.550	21.590	0.439	62.720	57.827
104947/104912	50.000	82.931	21.590	0.445	62.720	57.827
11162/11300	41.275	76.200	18.009	0.326	52.000	56.000
11163/11300	41.275	76.200	18.009	0.332	52.000	56.000
11590/11520	15.875	42.862	14.288	0.101	17.600	17.600
12303	18.000	47.000	14.383			
12435	26.000	59.000	17.500			
12648/12610	22.225	50.005	17.526	0.161	33.806	24.910
1280/1220	22.225	57.150	22.225	0.280		
13682/13620	36.512	69.012	19.050	0.307	42.703	36.475
13687/13620	38.100	69.012	19.050	0.285	52.500	67.900
14116/14274	30.226	69.012	19.845	0.362	43.148	35.808
14117A/14274	30.000	69.012	19.845	0.358	50.600	61.700
14118/14274 A	30.000	68.956	19.845	0.297	50.600	61.700
14124/14283	31.750	72.085	44.785	0.431	43.148	35.808
14125 A/14276	31.750	69.102	19.845	0.349		
14131/14276	33.338	69.012	19.845	0.336	53.900	67.000
14131/14283	33.338	72.085	22.385	0.419	43.148	35.808
14137 A/14276	34.925	69.012	19.845	0.323	53.900	67.000
14585/14525	34.925	68.262	20.638	0.312	54.800	68.100
15100/15245	25.400	62.000	19.050	0.292	47.400	86.000
15100S/15250	25.400	63.500	20.638	0.330	47.400	86.000
15101/15245	25.400	62.000	19.050	0.292	48.400	57.000
15102/15250 X	25.400	63.500	20.637	0.330	46.800	53.900
15103 S/15243	26.162	61.192	19.050	0.290	56.000	57.000
15103 S/15245	26.162	62.000	19.050	0.290	56.000	57.000
15116/15245	30.112	61.999	19.050	0.265	46.800	53.900
15117/15250	30.000	63.500	20.638	0.297	46.800	53.900
15119/15245	30.213	61.999	19.050	0.264	48.400	57.000
15123/15243	31.750	61.912	19.050	0.240	56.000	57.000
15123/15245	31.750	62.000	18.161	0.238	56.000	57.000

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
15125/15250	31.750	63.500	20.638	0.281	46.800	53.900
15126/15245	31.750	62.000	19.050	0.246	46.800	53.900
15126/15250 X	31.750	63.500	20.638	0.276		
15578/15520	25.400	57.150	17.462	0.210	40.200	45.500
15580/15523	26.988	60.325	19.842	0.258	42.600	50.100
16150/16283	38.100	72.238	23.812	0.382	56.000	60.000
16150/16284	38.100	72.238	20.638	0.350	56.000	60.000
17098/17244	24.981	61.999	16.002	0.250	40.000	44.100
1779/1738	23.813	57.150	20.218	0.257	38.255	29.358
17887/17831	45.230	79.985	19.842	0.394	63.800	83.300
18590/18520	41.275	73.025	16.667	0.276	54.000	56.000
18690/18620	46.038	79.375	17.462	0.326	57.000	62.000
18780/18720	46.038	85.000	17.462	0.420	44.260	39.144
18790/18720	50.800	85.000	17.462	0.363	50.100	65.500
18790/18724	50.800	88.900	17.462	0.425	50.600	67.500
19150/19281	38.100	71.438	15.875	0.593	38.700	31.360
1982 F/1924 AVQ519*	27.500	57.150	19.845	0.220		
1985/1922	28.575	57.150	19.845	0.219	54.000	55.000
1986/1922	25.400	57.150	19.845	0.238	44.800	50.200
1987/1922	26.975	57.150	19.845	0.228		
1988/1922	28.575	57.150	19.845	0.212	47.300	55.000
212047/212010	63.500	122.238	38.100	1.932		
212049/212010	66.675	122.238	38.100	1.842	169.032	153.464
212049/212011	66.675	122.238	38.100	1.842	169.032	153.464
23092/23256	23.812	65.088	22.225	0.366	50.600	55.800
23690/23620	34.925	73.025	26.988	0.508	88.000	93.000
24780/24720	41.275	76.200	22.225	0.419	68.200	86.500
25570/25519	36.513	82.550	23.813	0.653	68.503	60.941
25572/25520	38.100	82.931	23.813	0.644	76.500	98.200
25577/2/25520/2	42.875	82.931	23.812	0.581	80.900	106.000
25577/2/25523/2	42.875	82.931	26.987	0.626	80.900	106.000
25577/25521	42.875	83.058	23.812	0.569	80.900	106.000
25578/25521	42.862	83.058	23.812	0.570	83.800	111.000
25578/25523	42.862	82.931	26.988	0.613	83.800	111.000
25580/25520	44.450	82.931	23.812	0.545	80.900	106.000
25580/25521	44.450	82.058	23.812	0.548	80.900	106.000
25580/25522	44.450	83.058	23.876	0.548	80.900	106.000
25580/25523	44.450	82.931	26.988	0.591	80.900	106.000
25580/25526	44.450	85.001	23.813	0.599	83.800	111.000
25581/25522	44.450	83.058	23.876	0.562	80.900	106.000
25584/25521	44.983	83.058	23.813	0.550	83.800	111.000
25584/25527	44.983	85.000	26.988	0.649	83.800	111.000
25590/25520	45.618	82.931	23.812	0.529		
25590/25522	45.618	83.058	23.876	0.532		
25590/25523	45.618	82.931	26.988	0.575	80.900	106.000

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
2578/2520	28.575	66.421	24.606			
2581/2520	33.338	66.421	25.400	0.389		
2585/2520	33.338	66.421	25.400	0.386	77.500	94.400
25877/2/25821/2	34.925	73.025	23.812	0.471	72.100	88.000
25877/25821	34.925	73.025	23.812	0.456		
25880/25820	36.487	73.025	23.812	0.440	83.000	88.000
26877/26822	36.513	79.375	23.813	0.590	68.947	60.941
26881/26830	39.688	80.167	25.400	0.585	84.300	110.000
26882/26821	41.275	80.167	29.370	0.621	84.300	110.000
26884/26820	42.875	80.167	25.400	0.540	84.300	110.000
26885/26820	41.275	80.167	25.400	0.562	68.947	60.941
26886/26823	42.875	76.200	25.400	0.467	68.947	60.941
2690/2631	38.765	66.421	23.813	0.404	71.000	81.700
27680/27620	73.025	125.412	25.400	1.320	109.000	178.000
27684/27620	76.200	125.412	25.400		109.000	178.000
2776/2735X	38.100	73.025	23.813	0.442	80.400	102.000
2780/2729	36.487	76.200	23.812	0.500	65.389	56.492
2780/2735	36.487	73.025	23.813	0.467	65.389	56.492
2786/2735	34.925	73.025	23.813	0.476	80.400	102.000
2788/2720	38.100	76.200	23.812	0.496	86.500	93.000
2790/2729	33.338	76.200	23.813	0.553	80.400	102.000
2790/2735	33.338	73.025	23.813	0.499	80.400	102.000
2793/2729	34.925	76.200	23.813	0.540	80.400	102.000
2793/2735	34.925	73.025	23.813	0.485	80.400	102.000
2794/2729	36.487	76.200	23.813	0.517	65.389	56.492
28576/28521	44.869	92.075	24.607	0.789	75.175	71.172
28579/28521	50.000	92.075	24.607	0.717	91.600	130.000
28678/28622 B	50.800	97.630	24.608	0.830	102.000	129.000
28990/28920	61.976	101.600	24.607	0.767	80.958	81.402
29675/29620/3	69.850	112.713	25.400	0.948	114.000	156.000
29675/29630	69.850	120.650	25.400	1.161	102.000	166.000
29680/29630	70.637	120.650	25.400	1.143	85.851	91.189
29685/2/29620/3	73.025	112.712	25.400	0.871	114.000	156.000
29685/29630	73.025	120.650	25.400	1.084	114.000	156.000
302/28	28.000	58.000	17.250	0.250	38.000	41.500
30202	15.000	35.000	11.750	0.053	12.500	11.800
30202-A	15.000	35.000	11.750	0.530	14.200	13.500
30203	17.000	40.000	13.250	0.074		
30204	20.000	47.000	15.250	0.120	32.000	28.000
30205	25.000	52.000	16.250	0.150		
30206	30.000	62.000	17.250	0.220		
30207	35.000	72.000	18.250	0.320		
30208	40.000	80.000	19.750	0.410		
30208 B	40.000	80.000	19.750	0.432		
30209	45.000	85.000	20.750	0.460	76.500	76.500
30210	50.000	90.000	21.750	0.529		

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
30211	55.000	100.000	22.750	0.687		
30212	60.000	110.000	23.750	0.869		
30213	65.000	120.000	24.750	1.103		
30214	70.000	125.000	26.250	1.222		
30215	75.000	130.000	27.250	1.347		
30216	80.000	140.000	28.250	1.600		
30217	85.000	150.000	30.500	2.050		
30218	90.000	160.000	32.500	2.550		
30219	95.000	170.000	34.500	3.000	216.000	275.000
30220	100.000	180.000	37.000	3.650		
30221	105.000	190.000	39.000	4.220		
30222	110.000	200.000	41.000	5.000	308.000	405.000
30224	120.000	215.000	43.500	6.250	341.000	465.000
30226	130.000	230.000	43.750	7.000	369.000	490.000
30228	140.000	250.000	45.750	8.650	418.000	570.000
30230	150.000	270.000	49.000	11.000	429.000	560.000
30302	15.000	42.000	14.250	0.095	22.400	20.000
30303	17.000	47.000	15.250	0.130	28.100	25.000
30304	20.000	52.000	16.250	0.170	39.000	32.500
30305	25.000	62.000	18.250	0.260	44.600	43.000
30306	30.000	72.000	20.750	0.390		
30307	35.000	80.000	22.750	0.520		
30308	40.000	90.000	25.250	0.720		
30309	45.000	100.000	27.250	0.970		
30310	50.000	110.000	29.250	1.250		
30311	55.000	120.000	31.500	1.530		
30312	60.000	130.000	33.500	1.950		
30313	65.000	140.000	36.000	2.400		
30314	70.000	150.000	38.000	3.000		
30315	75.000	160.000	40.000	3.570	246.000	290.000
30316	80.000	170.000	42.500	4.340	270.000	320.000
30317	85.000	180.000	44.500	4.850	303.000	365.000
30318	90.000	190.000	46.500	5.650	330.000	400.000
30319	95.000	200.000	49.500	6.700	330.000	390.000
30320	100.000	215.000	51.500	8.050	402.000	490.000
30321	105.000	225.000	53.500	9.150	429.000	530.000
30322	110.000	240.000	54.500	11.000	473.000	585.000
30322-A	110.000	240.000	54.500	11.000	480.000	590.000
30324	120.000	260.000	59.500	14.000	561.000	710.000
30324-A	120.000	260.000	59.500	14.000	570.000	720.000
30326	130.000	280.000	63.750	17.000	627.000	800.000
30328	140.000	300.000	67.750	21.000	737.000	950.000
30330	150.000	320.000	72.000	28.500	825.000	1060.000
31305	25.000	62.000	18.250	0.260	38.000	40.000
31306	30.000	72.000	20.750	0.390	55.000	50.000
31307	35.000	80.000	22.750	0.520	71.000	67.000

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
31308	40.000	90.000	25.250	0.720	85.000	81.500
31309	45.000	100.000	27.250	0.950	106.000	102.000
31310	50.000	110.000	29.250	1.200	122.000	120.000
31311	55.000	120.000	31.500	1.550		
31312	60.000	130.000	33.500	1.830		
31313	65.000	140.000	36.000	2.350		
31314	70.000	150.000	38.000	2.950		
31315	75.000	160.000	40.000	3.500		
31316 J1	80.000	170.000	42.500	4.050	260.000	265.000
31317	85.000	180.000	44.500	4.600	242.000	285.000
31318	90.000	190.000	46.500	5.500		
31319	95.000	200.000	49.500	6.950	292.000	355.000
31320 X/CL7CVQ051 *	100.000	215.000	56.500	8.600	430.000	465.000
31322 X	110.000	240.000	63.000	12.000	457.000	585.000
31324 X	120.000	260.000	68.000	15.500	539.000	695.000
31326 X	130.000	280.000	72.000	18.500	605.000	780.000
31328 X	140.000	300.000	77.000	24.500	693.000	900.000
31330 X	150.000	320.000	82.000	29.500	781.000	1020.000
31594/31520	34.925	76.200	29.370	0.620		
3196/3130	33.338	72.626	30.163	0.581	76.065	62.720
320/22 X	22.000	44.000	15.000	0.105	25.100	29.000
320/28 X	28.000	52.000	16.000	0.145	36.500	38.000
320/32 X	32.000	58.000	17.000	0.195		
32004 X	20.000	42.000	15.000	0.097	28.000	27.000
32005 X	25.000	47.000	15.000	0.109	31.000	32.500
32006 X	30.000	55.000	17.000	0.170	40.500	44.000
32007	35.000	62.000	18.000	0.220	43.000	49.000
32007 X	65.000	62.000	18.000	0.220		
32007 XR	35.000	62.000	18.000	0.219		
32008 X	40.000	68.000	19.000	0.270		
32008 XRVA621 *	40.000	68.000	19.000	0.270	60.000	71.000
32008 XTN9	40.000	68.000	19.000	0.270	60.000	71.000
32008/38 X	38.000	68.000	19.000	0.270	60.000	71.000
32009 X	45.000	75.000	20.000	0.330		
32010 X	50.000	80.000	20.000	0.365		
32011 X	55.000	90.000	23.000	0.550		
32012 X	60.000	95.000	23.000	0.578		
32013 X	65.000	100.000	23.000	0.620		
32014 X	70.000	110.000	25.000	0.820		
32015	75.000	115.000	25.000	0.872		
32016 X	80.000	125.000	29.000	1.246		
32017 X	85.000	130.000	29.000	1.325		
32018 X	90.000	140.000	32.000	1.707		
32019 X	95.000	145.000	32.000	1.790		
32020 X	100.000	150.000	32.000	1.845		

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
32021 X	105.000	160.000	35.000	2.500		
32022 X	110.000	170.000	38.000	2.960		
32024 X	120.000	180.000	38.000	3.280		
32026 X	130.000	200.000	45.000	4.950	314.000	540.000
32028 X	140.000	210.000	45.000	5.400		
32030 X	150.000	225.000	48.000	6.350	369.000	655.000
322/28 B	28.000	58.000	20.250	0.250	48.000	50.000
32205 B	25.000	52.000	19.250	0.195	41.500	44.000
32206	30.000	62.000	21.250	0.280		
32206 BCL7CVA606 *	30.000	62.000	21.250	0.300		
32207	35.000	72.000	24.250	0.426		
32208	40.000	80.000	24.750	0.514		
32208 B	40.000	80.000	24.750	0.520	86.500	93.000
32209	45.000	85.000	24.750	0.558		
32210	50.000	90.000	24.750	0.601		
32210/45 BVB022 *	45.000	90.000	24.750	0.650	95.000	104.000
32211	55.000	100.000	26.750	0.830		
32212	60.000	110.000	29.750	1.119		
32212 B	60.000	110.000	29.750	1.150	140.000	156.000
32213	65.000	120.000	32.750	1.472		
32214	70.000	125.000	33.250	1.558		
32215	75.000	130.000	33.250	1.652		
32216	80.000	140.000	32.250	2.098		
32217	85.000	150.000	38.500	2.524		
32218 F	90.000	160.000	42.500	3.300		
32219	95.000	170.000	45.500	3.962		
32220	100.000	180.000	49.000	4.900		
32221	105.000	190.000	53.000	6.070		
32222	110.000	200.000	56.000	7.100	402.000	570.000
32224	120.000	215.000	61.500	9.150	468.000	695.000
32226	130.000	230.000	67.750	11.500	550.000	830.000
32228	140.000	250.000	71.750	14.500	644.000	1000.000
32230	150.000	270.000	77.000	17.500	737.000	1140.000
32303	17.000	47.000	20.250	0.170	40.000	33.500
32304	20.000	52.000	22.250	0.221		
32305	25.000	62.000	25.250	0.357		
32306	32.000	72.000	28.750	0.536		
32307	35.000	80.000	32.750	0.721		
32308	40.000	90.000	35.250	1.009		
32309	45.000	100.000	38.250	1.355		
32309 BR	45.000	100.000	38.250	1.450	156.000	176.000
32310	50.000	110.000	42.250	1.780		
32311	55.000	120.000	45.500	2.340		
32311 BR	55.000	120.000	45.500	2.500	216.000	260.000
32312	60.000	130.000	48.500	2.800		
32313	65.000	140.000	51.000	3.490	264.000	335.000

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
32313 B	65.000	140.000	51.000	3.715		
32314	70.000	150.000	54.000	4.100		
32314 B	70.000	150.000	54.000	4.510		
32315	75.000	160.000	58.000	5.200	336.000	440.000
32316	80.000	170.000	61.500	6.200	380.000	500.000
32317	85.000	180.000	63.500	6.850	391.000	560.000
32318	90.000	190.000	67.500	8.400	457.000	610.000
32319	95.000	200.000	71.500	11.000	501.000	670.000
32320	100.000	215.000	77.500	12.500	572.000	780.000
32321	105.000	225.000	81.500	14.500	605.000	815.000
32322	110.000	240.000	84.500	17.000	627.000	830.000
32324	120.000	260.000	90.500	21.500	792.000	1120.000
32326	130.000	280.000	98.750	26.600	858.000	1180.000
32328	140.000	300.000	107.750	33.900	1180.000	1720.000
32330	150.000	320.000	114.000	41.400	1170.000	1660.000
32907	35.000	55.000	14.000	0.123	2.570	2.480
32908	40.000	62.000	15.000	0.161	3.110	3.040
32909	45.000	68.000	15.000	0.187	3.220	3.280
32910	50.000	72.000	15.000	0.193	3.330	3.500
32911	55.000	80.000	17.000	0.282	4.140	4.560
32912	60.000	85.000	17.000	0.306	4.280	4.860
32913	65.000	90.000	17.000	0.323	4.390	5.140
32914	70.000	100.000	20.000	0.494	6.590	7.200
32916	80.000	110.000	20.000	0.560	7.060	8.120
32917	85.000	120.000	23.000	0.800	9.000	10.300
32918	90.000	125.000	23.000	0.838	9.330	10.900
32919	95.000	130.000	23.000	0.877	9.650	11.500
32920	100.000	140.000	25.000	1.150	11.700	13.500
32921	105.000	145.000	25.000	1.230	11.800	14.000
32922 X	110.000	150.000	25.000	1.250	12.000	14.300
32924	120.000	165.000	29.000	1.770		
32926	130.000	180.000	32.000	2.400	18.600	22.900
32928	140.000	190.000	32.000	2.550	19.100	24.100
32930	150.000	210.000	38.000	3.800	26.500	33.300
33005	25.000	47.000	17.000	0.131	28.000	23.900
33006	30.000	55.000	20.000	0.208	38.000	33.500
33007	35.000	62.000	21.000	0.267	45.500	41.000
33008	40.000	68.000	22.000	0.322	53.500	50.500
33009	45.000	75.000	24.000	0.414	59.500	57.500
33010	50.000	80.000	24.000	0.460	80.000	102.000
33011	55.000	90.000	27.000	0.670		
33012	60.000	95.000	27.000	0.710	106.000	143.000
33013	65.000	100.000	27.000	0.770		
33014	70.000	110.000	31.000	1.100	130.000	196.000
33015	75.000	115.000	31.000	1.118		
33016	80.000	125.000	36.000	1.700		

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
33017	85.000	130.000	36.000	1.681		
33018	90.000	140.000	39.000	2.250		
33019	95.000	145.000	39.000	2.240		
33020	100.000	150.000	39.000	2.500		
33021	105.000	160.000	43.000	2.970		
33022	110.000	170.000	47.000	3.850		
33024	120.000	180.000	48.000	4.200	292.000	540.000
33030	150.000	225.000	59.000	8.150	457.000	865.000
33108	40.000	75.000	26.000	0.510		
33109	45.000	80.000	26.000	0.560		
33110	50.000	85.000	26.000	0.600		
33111	55.000	95.000	30.000	0.880		
33112	60.000	100.000	30.000	0.940	134.000	170.000
33113	65.000	110.000	34.000	1.280		
33114	70.000	120.000	37.000	1.700		
33115	75.000	125.000	37.000	1.731		
33116	80.000	130.000	37.000	1.818		
33117	85.000	140.000	41.000	2.500		
33118	90.000	150.000	45.000	3.030		
33122	110.000	180.000	56.000	5.550	369.000	630.000
331257	40.000	95.000	27.250		83.300	101.800
33205	25.000	52.000	22.000	0.214		
33206	30.000	62.000	25.000	0.360		
33207	35.000	72.000	28.000	0.510		
33208	40.000	80.000	32.000	0.715		
33209	45.000	85.000	32.000	0.785		
33210	50.000	90.000	32.000	0.837		
33211	55.000	100.000	35.000	1.200		
33212	60.000	110.000	38.000	1.498		
33213	65.000	120.000	41.000	1.903		
33213 TN9	65.000	120.000	41.000	2.050	194.000	270.000
33214	70.000	125.000	41.000	2.044		
33215	75.000	130.000	41.000	2.270		
33216	80.000	140.000	46.000	2.851		
33217	85.000	150.000	49.000	3.700		
33219	95.000	180.000	58.000	5.500	374.000	560.000
33220	100.000	180.000	63.000	6.725		
33225/33462	57.150	117.475	30.162	1.578		
33281/33462	71.438	117.475	30.162	1.193		
33287/33462	73.025	117.475	30.162	1.150		
3379/3325	34.925	80.000	29.370	0.721		
3386/3320	39.688	80.167	29.370	0.650	106.000	129.000
33885/33822	44.450	95.250	27.783	0.940		
33891/33822	52.388	95.250	27.783	0.844	96.082	86.296
33895/33821	53.975	95.250	27.783	0.776		
34274/34478	69.952	121.442	24.607	1.102	94.600	136.000

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
34274/34492 A	69.952	125.052	23.731	1.170	94.600	136.000
34275/34492 A	70.000	125.052	23.731	1.170	94.600	136.000
34306/34478	77.788	121.442	24.608	0.893		
34306/34492 A	77.788	125.052	23.731		94.600	136.000
34307/34478	77.788	121.442	24.608		94.600	136.000
3479/3420	36.513	79.375	29.370	0.703	96.900	119.000
3482/3420	34.925	79.375	29.370	0.726	96.900	119.000
3490/3420	38.100	79.375	29.370	0.643		
350 A/354 A	40.000	85.001	20.638	0.558	62.275	49.820
355 A/354 A	44.450	85.001	20.638	0.508	62.275	49.820
355 X/352	44.450	90.119	23.000	0.670		
357/354 X	40.000	85.001	20.638	0.558	62.275	49.820
3576/3525	41.275	87.312	30.163	0.830	105.000	134.000
3577/3520	41.275	84.138	30.162	0.735	84.961	73.840
3579/3520	42.862	84.138	30.163	0.721	84.961	73.840
358 X/354 X	45.000	85.000	20.638	0.500		
3580/3520	38.100	84.138	30.163	0.798	84.961	73.840
3585/3520	41.275	84.138	30.163	0.753	84.961	73.840
3585/3525	41.275	87.312	30.162	0.812		
3586/3520	45.237	84.138	30.163	0.685	105.000	0.000
3586/3525	45.237	79.975	30.162	0.755		
359 S/352	46.038	90.119	23.000	0.649	62.275	49.820
359 S/354 X	46.038	85.000	20.638	0.488		
365/362 A	50.000	88.900	20.637	0.630	68.503	56.492
367/362	45.000	90.000	20.000	0.599	68.503	56.492
368 A/362 X	50.800	90.000	25.000	0.491		
369 S/2/362 A/2	47.625	88.900	20.638	0.558	76.500	91.500
37425/2/37625/2	107.950	158.750	23.020	1.400	101.000	163.000
37431/37625	109.538	158.750	23.020	1.289	101.000	163.000
3775/3720	50.800	93.264	30.162	0.840	113.000	153.000
3775/3730	50.800	93.264	30.163	0.853	113.000	153.000
3779/3732	47.625	98.425	30.163	1.048	113.000	153.000
3780/3720	50.800	93.264	30.162	0.829		
3780/3730	50.800	93.264	30.163	0.848	113.000	153.000
3781/3720	49.212	93.264	30.163	0.875	113.000	153.000
3784/3720	50.800	93.264	30.162	0.829	113.000	153.000
3784/3730	50.800	93.264	30.162	0.839	113.000	153.000
387 A/382 S	57.150	96.838	25.400	0.640		
387/382	57.150	98.425	21.000	0.612		
387/382 A	57.150	96.838	21.000	0.567	80.900	102.000
3872/3820	34.925	85.725	30.163	0.898	94.302	83.182
3872/3821	34.925	85.725	30.163	0.898	115.000	148.000
3877 A/3821	41.275	85.725	30.163	0.812		
389 A/382 A	53.975	96.838	21.000	0.615		
392/394 A	61.192	110.000	22.000	0.839	80.068	73.396
395 A/394 A	66.675	110.000	22.000	0.757		

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
39573/39521	50.800	112.712	30.163	1.542	155.000	224.000
39575/39520	50.800	112.712	30.163	1.542	155.000	224.000
39580/39520	57.150	112.712	30.162	1.361		
39580/39528	57.150	119.985	32.750	1.691		
39581/39520	57.150	112.712	30.162	1.361		
39581/39521	57.150	112.712	30.163	1.397	124.105	119.657
39581/39528	57.150	119.985	32.750			
39585/39521	63.500	112.712	30.163	1.270	124.105	119.657
39586/39521	65.001	112.712	30.163	1.250	124.105	119.657
39586/39528	64.988	119.985	32.751		155.000	224.000
39590/39521	66.675	112.712	30.163	1.184	155.000	224.000
39590/39528	66.675	119.985	32.750			
396/394 A	50.000	110.000	21.999	1.057	80.068	73.396
3975/3925	50.800	112.712	30.163	1.538	106.757	106.313
3977/3921	60.000	109.985	29.751		129.000	191.000
398/394 AS	50.800	110.000	21.999	1.039	80.068	73.396
3982/3920	63.500	112.712	30.162	1.217		
3984/2/3920/2	66.675	112.712	30.162	1.184		
408215	90.000	140.000	23.750			
415/414	38.100	88.500	26.988	0.839	85.406	68.058
418/414	38.100	88.500	26.988	0.817		
420/414	40.000	88.501	26.988	0.812	85.406	68.058
42350/42584	88.900	148.430	28.575	1.950	151.000	241.000
42350/42587	88.900	149.225	28.575	2.109	151.000	241.000
42683/42620	73.025	127.000	30.163	1.538	149.000	222.000
42687/42620	76.200	127.000	30.163	1.456	138.000	204.000
42690/42620	77.788	127.000	30.163	1.414	149.000	222.000
4375/4335	38.100	90.488	39.688	1.315	122.326	111.206
438/429	44.450	90.000	30.958			
4388/4335	41.275	90.488	39.687	1.248	135.000	174.000
4395/4335	42.070	90.488	39.687	1.234	122.326	111.206
441026 A	55.000	100.000	56.300			
44158/44348	39.688	88.501	25.400	0.685	77.900	88.600
44640/44610	23.813	50.292	14.224	0.132		
45280/45221	44.450	104.775	30.162	1.352	116.988	106.313
45291/45220	57.150	104.775	30.162	1.089	142.000	189.000
455 S/454	50.800	110.000	27.795	1.361	103.199	92.078
4580/2/4535/2	50.800	104.775	39.688	1.650	157.000	224.000
460/453 A	44.450	107.950	27.782	1.343	103.199	92.078
46176/46368	44.450	93.662	31.750	1.034	126.000	156.000
462/453 X	57.150	104.775	30.162	1.025	115.000	148.000
467/454	47.625	110.000	27.795		103.199	92.078
468/453 X	52.388	104.775	30.162	1.161	103.199	92.078
47487/20	69.850	120.000	32.545	1.497	154.000	228.000
47487/47420	69.850	120.000	32.545	1.460		
47490/47420	71.438	120.000	32.545	1.410	154.000	228.000

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
475/472 A	55.000	120.000	29.002	1.628	114.764	109.426
47678/47620	76.200	0.133	33.338	1.900	165.000	260.000
47679/47620	76.200	133.350	33.337	1.967	167.000	262.000
47680/47620	76.200	133.350	33.337	1.932		
47685/47620	82.550	133.350	33.337	1.757	167.000	262.000
47687/47620	82.550	133.350	33.338	1.757	167.000	262.000
477/472 A	63.500	120.000	29.002	1.447	114.764	109.426
478/472 A	65.000	120.000	29.002	1.411	114.764	109.426
47896/47820	95.250	146.050	33.338	1.941	168.000	280.000
479/472 A	66.675	120.000	29.002	1.370	114.764	109.426
482/472	69.850	120.000	29.795	1.267	132.000	186.000
48282/48220	120.650	182.562	39.689	3.692	202.394	260.221
48290/48220	127.000	182.562	39.688	3.320	229.000	440.000
48385/48320	133.350	190.500	39.687	3.620	262.000	542.000
48548/48514	34.925	68.262	38.100		54.000	57.000
48684/48620	142.875	200.025	41.275	3.833	265.000	560.000
48685/48620	142.875	200.025	41.275	3.869	265.000	560.000
4T K-43125/K-43312	31.750	79.375	25.400			
503809 [803904]						
50KW/3720	50.000	93.264	30.162			
522380	50.813	100.000	35.000			
52387/52637	98.425	161.925	36.512	2.857	207.000	343.000
524850	80.000	130.000	34.800			
525/522	38.100	101.600	34.925	1.479	120.992	104.533
526/522	41.275	101.600	34.925	1.424		
527053 C	54.500	104.775	36.513			
527056 C	30.000	62.000	24.000			
528 R/522	47.625	101.600	34.925	1.302		
528946	105.000	170.000	38.000			
528983	70.000	130.000	57.000			
53178/53377	44.450	95.250	30.958	0.899		
534565	70.000	130.000	57.000			
535/532 A	44.450	107.950	38.100	1.850	151.000	190.000
535/532 X	44.450	107.950	38.100	1.700	151.000	190.000
5356/5335	44.450	103.188	43.657	1.869	197.000	267.000
5358/5335	47.625	103.188	43.657	1.792	197.000	267.000
536/532 X	47.625	107.950	36.512	1.567	126.774	111.650
537/532 X	50.800	107.950	36.512	1.497		
539/532 A	53.975	111.125	38.100	1.615	151.000	190.000
539/532 X	53.975	107.950	36.512	1.430	151.000	190.000
554/553 X	61.912	122.238	38.100	1.969	142.343	133.447
555 S/552 A	57.150	123.825	38.100	2.150	142.343	133.447
555/553 X	50.800	122.238	38.100	2.250	142.343	133.447
559/553 X	63.500	122.238	38.100	1.919	142.343	133.447
560/553 X	66.675	122.238	38.100	1.828	142.343	133.447
565/562	63.500	130.048	36.512	1.928	177.200	206.100

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
566/563	69.850	127.000	36.512	1.870	173.000	249.000
567/563	73.025	127.000	36.512	1.806		
569/563	64.963	127.000	36.512	2.059	146.791	140.119
57414	40.988	67.975	17.500			
575/572	76.200	139.700	36.512	2.305		
576/572	73.025	139.992	36.513			
577/572	74.612	139.992	36.513	2.472		
580/572	82.550	139.992	36.512	2.100		
581/572	80.963	139.990	36.513	2.228	160.136	162.360
592/594	95.250	152.400	39.688	2.590		
593/592 A	88.900	147.640	35.717	2.359		
594/592 A	95.250	152.400	39.688	2.426		
595 A/592 XS	79.375	147.638	35.717		162.360	169.032
595/593 X	82.550	150.000	35.992	0.369	162.360	169.032
596/592 A	85.725	152.400	39.688	2.889	162.360	169.032
598 A/592 A	92.075	152.400	39.688	2.491		
598/592 A	92.075	152.400	39.688	2.700		
623/614 X	57.150	115.000	41.021	1.850		
636/633	53.975	130.175	41.275	2.790	173.481	162.360
6379/6320	65.088	135.755	53.975	3.500		
6379/K-6320	65.088	135.755	53.975	3.710	286.000	400.000
6380/6320	54.813	135.755	53.975		298.000	404.000
6381/6320	54.988	135.755	53.975	4.132	246.876	235.756
6382/6320	63.500	135.755	53.975	3.778	298.000	404.000
6386/K-6320	66.675	135.755	53.975	3.642	286.000	400.000
6389/6320	66.675	135.755	53.975	3.629	298.000	404.000
639/633	63.500	130.175	41.275	2.508	60.496	46.706
639297	28.000	57.150	17.662			
639330	39.000	71.996	21.500			
639337	33.338	76.200	29.370			
639338	34.925	76.200	29.370			
643/633	69.850	130.175	41.275	2.291	173.481	162.360
64432/64708	110.000	180.000	41.275	3.900	251.000	415.000
64450/64700	114.300	177.800	41.275	3.453	251.000	415.000
64450/64701 X	114.300	178.000	41.275	3.511	254.000	419.000
645/633	71.438	130.175	41.275	2.223	173.481	162.360
6461/6420					321.000	463.000
65231/65500	58.738	127.000	44.450	2.699	225.000	297.000
65235/65500	59.880	127.000	44.450	2.658	225.000	297.000
65390/65320	49.212	114.300	44.450	1.520	212.000	224.000
655/653	69.850	146.050	41.275	3.270		
6559/6535	82.550	161.925	53.975	5.070	343.000	523.000
6576/6525X	76.200	160.000	53.975		343.000	523.000
658/653 X	74.612	150.000	41.275	3.320		
6580/6525X	88.900	160.000	53.975	4.581	343.000	523.000
661/653	79.375	146.050	41.275	2.881	184.601	182.377

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
663/653	82.550	146.050	41.275	2.669		
665 A/653	85.725	146.050	41.275	2.580		
665/653	85.725	146.050	41.275	2.800	220.000	320.000
66589/66520	59.972	122.238	33.338			
67388/67322	127.000	196.850	46.038	5.080	319.000	585.000
67391/67322	133.350	196.850	46.038	4.800	319.000	585.000
677/672	85.725	168.280	41.275	4.159	200.170	209.066
68145/68111	35.000	59.974	15.875			
682/672	94.976	168.275	41.275			
683/672	95.250	198.275	41.275	3.600		
68450/68709	114.300	180.099	34.925	2.830	151.240	146.791
68450/68712	114.300	180.975	34.925	2.950	183.000	280.000
687/672	101.600	168.275	41.275	3.286		
69354/69630	89.992	160.096	30.124	2.325	167.000	230.000
7049/7010	70.000	130.000	43.000	2.332		
72200 C/72487	50.800	123.825	36.512	2.140		
72225 C /72487	57.150	123.825	36.512	1.980	167.000	208.000
740/743	80.962	150.000	44.455		233.532	224.634
745 A/742	69.850	150.089	44.450	3.910	233.532	224.634
745 S/743	63.500	150.000	44.455	4.119	233.532	224.634
74550/74850	139.700	215.900	47.625	5.920	354.000	614.000
748/743	80.000	150.000	44.455			
749/742	85.026	150.089	44.540	3.129		
749/743	85.026	150.000	44.455		233.532	224.634
750/743	79.375	150.000	44.455		233.532	224.634
756 A/752	79.375	161.930	47.625		242.428	237.980
762 XA/752	73.025	161.925	47.625	4.853	242.428	237.980
766/752	88.900	161.925	47.625	4.069	242.428	237.980
767 X/752	90.000	161.925	47.625	4.028	242.428	237.980
78250/78537	63.500	136.525	36.513	2.381	158.000	193.000
78250/78551	63.500	140.030	66.091	2.436	158.000	193.000
78349/78310	35.001	61.999	16.701	0.200	33.139	29.136
795/792	120.650	206.375	47.625	6.350	282.462	313.600
797/792	130.000	206.375	47.625	5.669	282.462	313.600
799/792	128.587	206.375	47.625	5.760	282.462	313.600
801023 AB	29.000	50.292	35.040			
801464 A	60.000	137.300	33.700			
807048/807010	54.500	104.745	36.512			
86643/86610	25.400	64.292	21.433	0.366		
86648/86510	30.995	64.292	21.433	0.333		
88540/88513	30.000	72.000	29.370			
88630/88610	25.400	72.233	25.400	0.575		
89440/89411	31.750	76.200	29.370	0.689		
89443/89411	33.338	76.200	29.370	0.671		
89444/89411	33.338	76.200	29.370	0.667		
89448/89411	36.512	76.200	29.369	0.630	42.703	36.475

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
90381/90744/HA1	96.838	188.913	53.297			
913849/10	69.850	146.050	41.275	2.848		
9285/9220/CL7C	76.200	161.925	49.212	4.400		
9380/9321	76.200	171.450	49.212	4.980	284.000	351.000
95500/95925	127.000	234.950	63.500	11.975	582.000	931.000
A 4059/A 4138	14.989	34.988	10.998	0.051	13.400	13.200
EK-M 84249/EK-M 84210	25.400	59.530	23.368	0.321		
H 212749/H 212710	65.987	123.975	41.500	2.091		
H 414249/210	71.438	136.525	41.275	2.622		
H 913842/810	61.912	146.050	41.275	3.098		
H 913843/810	61.912	146.050	41.275			
HM 204043/HM 204010	39.987	90.975	32.000	1.000		
HM 212047/HM 212011	63.500	122.238	38.100	1.960		
HM 212049/HM 212010	66.675	122.238	38.100	1.840		
HM 218248/HM 218210	89.974	146.975	40.000	2.515		
HM 218248/W/2A/210/2A	90.000	147.000	40.000	2.549	229.000	355.000
HM 220149/110	100.000	156.975	42.000	2.900	246.000	400.000
HM 220149/HM 220110	99.975	156.975	42.000	2.842		
HM 231132/110	139.700	236.538	57.150	10.000	512.000	850.000
HM 231148/110	149.225	236.538	57.150	10.000	512.000	850.000
HM 801346 X/2/310VQ523 *	38.100	82.550	29.370	0.770		
HM 801346/310	38.100	82.550	29.370	0.780		
HM 803146/110	41.275	88.900	30.162	0.894		
HM 803146/2/110/2	41.275	88.900	30.162	0.900		
HM 803149/110	44.450	88.900	30.162	0.844		
HM 807040/010	44.450	104.775	36.512	1.610		
HM 807046/010	50.800	104.775	36.512	1.500		
HM 88542/2/510/2	31.750	73.025	29.370	0.620		
HM 88542/510	31.750	73.025	29.370	0.617		
HM 88542/HM 88510	31.750	73.025	29.370	0.630		
HM 88648/610	35.717	72.233	25.400	0.476		
HM 88649/2/610/2	34.925	72.233	25.400	0.485		
HM 88649/HM 88610	34.925	72.233	25.400	0.480		
HM 89446/2/410/2	34.925	76.200	29.370	0.644		
HM 89449/2/410/2	36.512	76.200	29.370	0.630		
HM 903249/2/210/2	44.450	92.250	30.958	0.999		
HM 903249/HM 903210	44.450	95.250	30.958	0.954		
HM 903249/W/210	44.450	92.250	30.958	1.002		
HM 911245/W/2/210/2	60.325	130.175	36.512	2.109	176.000	180.000

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
HM 911245/W/210V001 *	60.325	130.175	36.512			
JF7049/7010	70.000	130.000	43.000	2.450		
JHM 720249/210	100.000	160.000	41.000	1.374		
JL 26749 F/710	32.000	53.000	14.500		27.000	35.500
JL 69345 A/310	38.000	63.000	17.000	0.203		
JL 69345 F/310	38.000	63.000	17.000	0.203		
JL 69345 X/310	38.000	63.000	17.000	0.203		
JL 69345/310	38.000	63.000	17.000	0.203		
JL 819349/JL 819310	95.000	135.000	20.000	0.829		
JLM 104948 AA/910 AA	50.000	82.000	21.500	0.194	83.000	100.000
JLM 508748/710	60.000	95.000	24.000	0.278		
JM 205149/110	50.000	90.000	28.000	0.340	122.000	140.000
JM 511946/910	65.000	110.000	28.000	0.490		
JM 515649/610	80.000	130.000	35.000	0.780		
JM 714249/210	75.000	120.000	31.000	0.581		
JM 718149 A/110	90.000	145.000	35.000	2.100		
JM 822049/JM 822010	110.000	165.000	35.000	1.139		
K 29586/29522	63.500	107.950	25.400		102.000	161.000
K 55175 C/55437	44.450	111.125	30.163	1.381	98.500	119.000
K-02473/K-02420	25.400	68.263	22.225	0.430	51.155	42.036
K-02474/K-02420	28.575	68.263	22.225	0.407	58.300	69.500
K-02475/K-02420	31.750	68.263	22.225	0.379	51.155	42.036
K-02876/K-02820	31.750	73.025	22.225	0.451	60.800	74.900
K-02877/K-02820	34.925	73.025	22.225	0.419	78.800	74.900
K-05079/K-05185	20.000	47.000	14.381	0.115	24.700	25.400
K-07087/K-07210	22.225	50.800	15.011	0.143		
K-07100S/K-07196	25.400	50.005	13.495	0.112	27.000	29.600
K-09067/K-09196	19.050	49.225	21.209	0.194	39.100	40.000
K-09081/K-09196	20.625	49.225	23.020	0.200	39.100	40.000
K-12580/K-12520	20.638	49.225	19.845	0.179	40.400	43.200
K-13685/K-13620	38.100	69.012	19.050	0.293	52.500	67.900
K-13687/K-13621	38.100	69.012	19.050	0.293	52.500	67.900
K-1380/K-1328	22.225	52.388	19.368	0.195		
K-1380/K-1329	22.225	53.975	19.368	0.211	36.253	27.357
K-14116/K-14276	30.226	69.012	19.845	0.365	50.600	61.700
K-14117A/K-14276	30.000	69.012	19.845	0.361	50.600	61.700
K-14118/K-14276	30.000	69.012	19.845	0.361	43.148	35.808
K-14118/K-14283	30.000	72.085	44.785			
K-14124/K-14276	31.750	69.012	19.845	0.354	50.600	61.700
K-14125/K-14274	31.750	69.012	19.845	0.347	50.600	61.700
K-14125/K-14276	31.750	69.012	39.705	0.351	50.600	61.700
K-14131/K-14274	33.338	69.012	19.845	0.347	50.600	61.700
K-14137A/K-14274	34.925	68.956	19.845	0.313		
K-14137A/K-14283	34.925	72.085	44.785			

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
K-14138 A/K-14274	34.925	68.956	19.845	0.321	53.900	67.000
K-15101/K-15250	25.400	63.500	20.637	0.330	48.400	57.000
K-15106/K-15245	26.988	61.999	19.050	0.288	46.800	53.900
K-15112/K-15245	28.575	61.999	19.050	0.274	48.400	57.000
K-15112/K-15250	28.575	63.500	20.637	0.281	48.400	57.000
K-15113/K-15245	28.575	61.999	19.050	0.276	46.800	53.900
K-15113/K-15250	28.575	63.500	20.638	0.308	46.800	53.900
K-15117/K-15245	30.000	61.999	19.050	0.265	46.800	53.900
K-15118/K-15245	30.213	61.999	19.050	0.262	48.400	57.000
K-15118/K-15250	30.213	63.500	20.638	0.294	48.400	57.000
K-15120/K-15245	30.213	61.999	19.050	0.264	46.800	53.900
K-15123/K-15250	31.750	63.500	19.749	0.270		
K-15125/K-15245	31.750	61.999	19.050	0.249	46.800	53.900
K-15590/K-15520	28.575	57.150	17.463	0.194	42.600	50.100
K-16150/K-16282	38.100	71.999	18.999	0.320	52.400	65.800
K-1755/K-1729	22.225	56.896	19.368	0.252	42.000	45.300
K-18685/K-18620	44.450	79.375	17.462	0.341	48.200	61.300
K-19150/K-19283	38.100	71.999	17.018	0.296	38.700	31.360
K-1986/K-1932	25.400	58.738	19.050	0.250	44.800	50.200
K-1997/K-1922	26.988	57.150	19.845	0.216	44.800	50.200
K-21075/K-21212	19.050	53.975	22.225	0.245		
K-23100/K-23256	25.400	65.088	22.225	0.356	50.600	55.800
K-24780/K-24721	41.275	76.200	25.400	0.467	69.900	89.200
K-25578/K-25520	42.862	82.931	23.813	0.581	83.800	111.000
K-25584/K-25520	44.983	82.931	23.813	0.553	83.800	111.000
K-25584/K-25523	44.983	82.931	26.988	0.599	83.800	111.000
K-2580/K-2520	31.750	66.421	25.400	0.405	69.300	81.500
K-2585/K-2523	33.338	69.850	23.813	0.432	70.400	133.200
K-25877/K-25820	34.925	73.025	23.813	0.467	72.100	88.000
K-25878/K-25820	34.925	73.025	23.813	0.467	78.800	97.400
K-25878/K-25821	34.925	73.025	23.813	0.467	78.800	97.400
K-25880/K-25821	36.487	73.025	23.813	0.454	72.100	88.000
K-26878/K-26820	38.100	80.167	25.400	0.603	68.947	60.941
K-26878/K-26822	38.100	79.375	23.813	0.567	84.300	110.000
K-26881/K-26822	39.688	79.375	23.813	0.549	84.300	110.000
K-26882/K-26822	41.275	79.375	23.813	0.526	84.300	110.000
K-26884/K-26822	42.875	79.375	23.813	0.463	84.300	110.000
K-26884/K-26823	42.875	76.200	25.400	0.467	84.300	110.000
K-27687/K-27620	82.550	125.412	25.400	1.095	112.000	186.000
K-2780/K-2720	36.487	76.200	23.813	0.517	65.389	56.492
K-2785/K-2729	33.338	76.200	23.813	0.553	80.400	102.000
K-2788/K-2729	38.100	76.200	23.813	0.499	74.800	93.000
K-2788/K-2735X	38.100	73.025	23.813	0.446	74.800	93.000
K-27881/K-27820	38.100	80.035	24.608	0.558	72.200	91.100
K-2789/K-2720	39.688	76.200	23.813	0.476	74.800	93.000
K-2789/K-2729	39.688	76.200	23.813	0.481	73.200	91.200

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
K-2789/K-2735X	39.688	73.025	23.813	0.424	74.800	93.000
K-2790/K-2720	33.338	76.200	23.813	0.548	80.400	102.000
K-2793/K-2720	34.925	76.200	23.813	0.535	80.400	102.000
K-2794/K-2720	36.487	76.200	23.813	0.513	74.800	93.000
K-2794/K-2735	36.487	73.025	23.813	0.463	74.800	93.000
K-2796/K-2720	34.925	76.200	23.813	0.531	80.400	102.000
K-2796/K-2729	34.925	76.200	23.813	0.535	80.400	102.000
K-28580/K-28521	50.800	92.075	24.607	0.703	84.200	116.100
K-28584/K-28521	52.388	92.075	24.607	0.676	85.800	118.000
K-28680/K-28622	55.562	97.630	24.608	0.771	89.700	129.000
K-28682/K-28920	57.150	101.600	25.400			
K-28985/K-28920	60.325	101.600	25.400	0.807	85.800	125.000
K-28985/K-28921	60.325	100.000	25.400	0.767	85.800	125.000
K-29688/K-29620	73.817	112.712	25.400	0.862	26.500	166.000
K-2984/K-2924	46.038	85.000	25.400	0.612	86.400	117.000
K-31593/K-31520	34.925	76.200	29.370	0.625		
K-31593/K-31521	34.925	76.200	29.370	0.630	87.700	107.000
K-31597/K-31520	36.513	76.200	29.370	0.608	85.800	106.000
K-31597/K-31521	36.513	76.200	29.370	0.612	87.700	107.000
K-3188/K-3120	31.750	72.626	30.162	0.593	79.300	144.100
K-3193/K-3120	31.750	72.626	30.162		87.700	102.000
K-3196/K-3120	33.338	72.626	30.163	0.576	87.700	102.000
K-33262/K-33462	66.675	117.475	30.162	1.353	123.000	190.000
K-33275/K-33462	69.850	117.475	30.162	1.275	123.000	190.000
K-33281/K-33472	71.438	120.000	29.794	1.311	123.000	190.000
K-33287/K-33472	73.025	120.000	29.794	1.270	123.000	190.000
K-336/K-332	41.275	80.000	21.000	0.467	60.496	46.706
K-337/K-332	38.100	80.000	24.176	0.535	60.496	46.706
K-3379/K-3320	34.925	80.167	29.370	0.725	106.000	129.000
K-33885/K-33821	44.450	95.250	27.783	0.980	120.000	161.000
K-33885/K-33822	44.450	95.250	27.783		105.000	137.000
K-33889/K-33822	50.800	95.250	27.783	0.871		
K-339/K-332	35.001	80.000	21.001	0.531	60.496	46.706
K-342/K-332	41.275	80.000	21.000	0.463	60.496	46.706
K-344/K-332	40.000	80.000	21.001	0.481		
K-3474/K-3420	30.163	79.375	29.370	0.780	96.900	119.000
K-3478/K-3420	34.925	79.375	29.370	0.721	91.300	110.000
K-350/K-352	40.000	90.119	23.000	0.717	62.275	49.820
K-355/K-352	44.450	90.119	23.000		62.275	49.820
K-3578/K-3520	44.450	84.138	30.163	0.694	105.000	134.000
K-3578/K-3525	44.450	87.312	30.163	0.776	105.000	134.000
K-3579/K-3525	42.862	87.312	26.992		102.000	132.000
K-366/K-362 A	50.000	88.900	20.637	0.526	68.503	56.492
K-37425/K-37625	107.950	158.750	23.020	1.356		
K-3767/K-3720	52.388	93.264	30.163	0.816		
K-3767/K-3730	52.388	93.264	30.163	0.821	113.000	153.000

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
K-3776/K-3720	44.983	93.264	30.163	0.948	110.000	146.000
K-3778/K-3720	47.625	93.264	30.163	0.894	113.000	153.000
K-3782/K-3720	44.450	93.264	30.163	0.957	110.000	146.000
K-3782/K-3730	44.450	93.264	30.163	0.962	110.000	146.000
K-385 A/K-383 A	50.800	100.000	21.000	0.748	69.837	59.606
K-385/K-382	50.800	98.425	21.000	0.748	69.837	59.606
K-386 A/K-382 A	47.625	96.838	21.000	0.717	80.900	102.000
K-387/K-383 A	57.150	100.000	21.000	0.662	80.900	102.000
K-3877/K-3820	41.275	85.725	30.163	0.807	115.000	148.000
K-3878/K-3820	36.513	85.725	30.163	0.880	115.000	148.000
K-388 A/K-382	57.531	98.425	21.000	0.621	80.900	102.000
K-390 A/K-394 A	63.500	110.000	22.000	0.846	80.068	73.396
K-395/K-394 A	63.500	110.000	21.000	0.844		
K-39585/K-39520	63.500	112.712	30.163	1.261	142.000	204.000
K-3979/K-3920	57.150	112.712	30.163	1.406	129.000	191.000
K-3980/K-3925	60.325	112.712	30.163		129.000	191.000
K-3982/K-3925	63.500	112.712	30.163		129.000	191.000
K-3984/K-3925	66.675	112.712	30.163	1.993	123.000	183.000
K-399 A/394 A	68.262	110.000	21.999	0.762		
K-41125/K-41286	28.575	72.626	24.608	0.474	64.600	64.100
K-419/K-414	41.275	88.500	26.988	0.789	101.000	114.000
K-42346/K-42584	87.960	148.430	28.575	1.982	151.000	241.000
K-42368/K-42584	93.662	148.430	28.575	1.801	151.000	241.000
K-42381/K-42584	96.838	148.430	28.575	1.683	151.000	241.000
K-42687/K-42620	76.200	127.000	30.163	1.468	138.000	204.000
K-42688/K-42620	76.200	127.000	30.163	1.429	138.000	204.000
K-438/K-432 A	44.450	95.250	27.783	0.953		
K-44162/K-44348	41.275	88.500	25.400	0.671	77.900	88.600
K-45284/K-45220	50.800	104.775	30.162	1.220		
K-456/K-453 X	53.975	104.775	30.162	1.125	103.199	92.078
K-4580/K-4535	50.800	90.488	39.687		157.000	224.000
K-462/K-454	57.150	110.000	27.795		115.000	148.000
K-467/K-453 A	47.625	107.950	27.782		103.199	92.078
K-46790/K-46720	165.100	225.425	41.275	4.672	281.000	635.000
K-469/K-453 X	57.150	104.775	30.162	1.061	115.000	148.000
K-476/K-472	60.000	120.000	29.794	1.551	114.764	109.426
K-47686/K-47620	82.550	133.350	33.338	1.757	165.000	260.000
K-47890/K-47820	92.075	146.050	33.338	2.068	182.000	307.000
K-480/K-472 A	68.262	120.000	29.002	1.329	114.764	109.426
K-483/K-472 A	63.500	120.000	29.002	1.447	114.764	109.426
K-48393/K-48320	136.525	190.500	76.995		262.000	542.000
K-484/K-472 A	70.000	120.000	29.002	1.293	132.000	186.000
K-49175/K-49368	44.450	93.662	31.750	1.016		
K-495/K-492 A	82.550	133.350	30.163	1.710	145.000	220.000
K-495/K-493	82.550	136.525	57.150	1.630	145.000	220.000
K-496/K-492 A	80.962	133.350	30.163		145.000	220.000

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
K-496/K-493	80.962	136.525	30.163	1.680	145.000	220.000
K-497/K-492	85.725	133.350	30.163	1.721		
K-497/K-493	85.725	136.525	57.150	1.537	145.000	220.000
K-498/K-492	84.138	133.350	30.162			
K-498/K-493	84.138	136.525	57.150	1.590	145.000	220.000
K-52400/K-52618	101.600	157.162	36.512	2.286	207.000	343.000
K-527/K-522	44.450	101.600	34.925	1.361		
K-529/K-522	50.800	101.600	34.925	1.229		
K-5395/K-5335	49.212	103.188	43.657	1.751	176.000	240.000
K-55187/K-55443	47.625	112.712	30.163	1.370	95.200	114.000
K-55200/K-55437	50.800	111.125	30.163	1.281	95.200	114.000
K-560/K-552	66.675	123.825	38.100	1.904		
K-56418/K-56650	106.362	165.100	36.512	2.767	210.000	355.000
K-56425/K-56650	107.950	165.100	36.512	2.610		
K-580/K-572 X	82.550	139.700	36.513	2.200	160.136	162.360
K-582/K-572	82.550	139.992	36.513	2.158		
K-621/K-612	53.975	120.650	41.275	2.209	168.000	212.000
K-623/K-612	57.150	120.650	41.275	2.118	212.000	186.000
K-641/K-632	66.675	136.525	41.275		196.000	264.000
K-641/K-633	66.675	130.175	41.275	2.404	173.481	162.360
K-643/K-632	69.850	136.525	41.275			
K-644/K-633	71.438	130.175	41.275	2.232	173.481	162.360
K-6460/K-6420	73.025	149.225	53.975	4.418	321.000	463.000
K-65200/K-65500	50.800	127.000	44.450	2.935	182.377	166.808
K-65212/K-65500	53.975	127.000	44.450	2.839	209.000	275.000
K-65237/K-65500	60.325	127.000	44.450	2.649	209.000	275.000
K-6580/K-6535	88.900	161.925	53.974	4.700	343.000	523.000
K-6581/K-6535	90.000	161.925	53.974		343.000	523.000
K-659/K-653	76.200	146.050	41.275		220.000	320.000
K-663/K-652	82.550	152.400	41.275	3.110	220.000	320.000
K-665 A/K-652	85.001	152.400	41.275	2.994	184.601	182.377
K-67390/K-67322	133.350	196.850	46.038	4.627	340.000	625.000
K-681/K-672	92.075	162.280	41.275	3.874	200.170	209.066
K-68462/K-68712	117.475	180.975	34.925	2.700	181.000	271.000
K-740/K-742	80.962	150.089	44.450			
K-749/K-742	85.026	150.089	44.450	3.210	286.000	405.000
K-755/K-752	76.200	161.925	47.625			
K-757/K-752	82.550	161.930	47.625	4.400	242.428	237.980
K-758/K-752	85.725	161.930	47.625	4.250	242.428	237.980
K-759/K-752	88.900	161.930	47.625	4.082	242.428	237.980
K-760/K-752	90.488	161.930	47.625	4.001	242.428	237.980
K-78215/K-78551	53.775	140.030	36.512		185.000	234.000
K-861/K-854	101.600	190.500	57.150	6.985	342.513	344.737
K-938/K-932	114.300	212.725	66.675	10.070	427.029	435.926
K-95525/K-95925	133.350	234.950	63.500	11.294	582.000	931.000

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
K-HM 518445/K-HM 518410	88.900	152.400	39.688	2.787		
K-HM 804840/K-HM 804810	41.275	95.250	30.163	1.080	97.861	91.633
K-HM 88547/K-HM 88510	33.338	73.025	29.370	0.599		
K-HM 88638/K-HM 88610	31.999	72.233	25.400	0.513		
K-HM 89443/K-HM 89410	33.338	76.200	29.370	0.667	78.100	106.000
K-HM 89446/K-HM 89411	34.925	76.200	29.369	0.653		
K-HM 89449/K-HM 89411	36.512	76.200	29.370	0.630	70.282	65.389
K-JHM 318448/K-JHM 318410	90.000	155.000	44.000	1.510		
K-JL 69349/K-JL 69310	38.000	63.000	17.000	0.090 LBS		
K-LM 29748/K-LM 29711	38.100	65.088	19.812	0.246	50.000	57.000
K-LM 501349/K-LM 501311	41.275	73.431	23.012	0.368	55.000	69.500
K-LM 67048/K-LM 67010	31.750	59.131	15.875	0.176		
K-LM 806649/K-LM 806610	53.975	88.900	19.050			
K-M 201047/K-M 201011	39.688	73.025	25.654	0.421	66.000	86.500
K-M 88046/K-M 88010	31.750	68.263	22.225	0.394	55.000	69.500
L 327249/210	133.350	177.008	25.400	1.800	134.000	280.000
L 44643/610	25.400	50.292	14.224	0.126		
L 44649/610	26.988	50.292	14.224	0.117		
L 44649/L 44610	26.880	50.292	14.224	0.115		
L 45449/410	28.999	50.292	14.224	0.109		
L 45449/L 45410	29.000	50.292	14.224	0.110		
L 68149/110	34.988	59.131	15.875	0.170		
L 68149/111	35.001	60.000	15.875	0.173		
L 814749/710	76.200	109.538	19.050	0.600		
LM 102949/910	45.242	73.431	19.558	0.304	62.000	75.000
LM 102949/LM 102910	45.242	73.431	19.558	0.300		
LM 104949/911	50.800	82.550	21.590	0.424	72.100	100.000
LM 104949/JLM 104910	50.800	82.000	21.976	0.406		
LM 104949/LM 104911	50.800	82.550	21.976	0.411		
LM 11749/710	17.463	39.878	13.843	0.081	24.500	20.800
LM 11749/710VC027 *	17.462	39.878	13.843	0.081	24.500	20.800
LM 11749/LM 11710	17.462	39.878	13.843	0.081		

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
LM 11949 RS/LM 11910	19.050	45.237	15.494	0.130		
LM 11949/910	19.050	45.237	15.494	0.119	31.500	27.500
LM 12748/710	21.430	45.237	15.494	0.120	27.500	31.000
LM 12749/710	21.999	45.999	15.494	0.121	31.500	31.000
LM 12749/711	21.986	45.974	15.494	0.120	31.500	31.000
LM 12749/LM 12710	21.986	45.237	15.494	0.120		
LM 29748/710	38.100	65.088	18.034	0.227	50.000	57.000
LM 29749/710CL7C-VA607 *	38.100	65.088	18.034	0.232	50.000	57.000
LM 29749/711	38.100	65.088	19.812	0.246	50.000	57.000
LM 29749/711CL7C-VA607 *	38.100	65.088	19.812	0.250	50.000	57.000
LM 300849/811	40.988	67.975	17.500	0.240	50.000	58.500
LM 48548 A/510	34.925	65.088	18.034	0.243	54.000	57.000
LM 48548 RS/LM 48510	34.925	65.088	18.034	0.280		
LM 48548/LM 48510	34.925	65.088	18.034	0.260		
LM 501349/2/310/2	41.275	73.431	19.558	0.330		
LM 501349/310	41.275	73.431	19.558	0.331		
LM 501349/314	41.275	73.431	21.430	0.351		
LM 501349/LM 501310	41.275	73.431	19.558	0.326		
LM 503349/310CL7C	46.000	75.001	18.000	0.293		
LM 603049/011	45.242	77.788	19.842	0.370		
LM 67048 RS/LM 67010	31.750	59.131	15.875	0.185		
LM 814849/2/810/2	77.788	117.475	25.400	0.900		
M 12649/610	21.430	50.005	17.526	0.166	42.500	38.000
M 12649/M 12610	21.430	50.005	17.526	0.170		
M 2010447/011	39.688	73.025	25.654	0.450	76.500	86.500
M 802048/011	41.275	82.550	26.543	0.640		
M 802048/M 802011	41.275	82.550	26.543	0.630		
M 84548/2/510/2VQ506 *	25.400	57.150	19.431	0.238		
M 86647/610	28.575	64.292	21.433	0.344		
M 86649/2/610/2VQ506 *	30.163	64.292	21.433	0.332		
M 88043/010/2	30.163	68.263	22.225	0.407		
M 88048/2/010/2	33.338	68.263	22.225	0.380		
M88040/M88010	28.575	68.263	22.225	0.420		
T 101	25.654	50.800	15.875	0.130		
T 113	28.829	55.562	15.875	0.145		
T 119	30.416	55.562	15.875	0.140		
T 126	32.004	55.562	15.875	0.140		
T 138	35.179	66.675	19.446	0.290		
T 144	36.754	66.675	19.446	0.270		

Tapered Roller Bearings- Single Row



BEARING REF.	DIMENSIONS			WEIGHT	BASIC LOAD RATINGS	
	d (mm)	D (mm)	B (mm)		DYNAMIC	STATIC
T 151	38.354	72.619	21.433	0.240		
T 163	41.529	72.619	21.433	0.350		
T 177	45.000	73.000	20.000	0.320		
T 182	46.279	82.956	23.812	0.495		
T 199	51.054	74.612	15.875	0.200		
T2DD 065	65.000	110.000	31.000	1.150		
T2ED 045	45.000	95.000	36.000	1.200	147.000	186.000
T2ED 050	50.000	100.000	36.000	1.300		
T2ED 055CLN	55.000	110.000	39.000	1.700		
T2ED 070CLNVB061	70.000	130.000	43.000	1.450		
T2EE 040VB134	40.000	85.000	33.000	0.900		
T2EE 060	60.000	115.000	40.000	1.850		
T2EE 100	100.000	165.000	47.000	3.900	314.000	480.000
T3FE 075VB481	75.000	145.000	52.000	3.950		
T4CB 100	100.000	145.000	24.000	1.150		
T4CB 120	120.000	170.000	27.000	1.700	157.000	250.000
T4CB 140	140.000	195.000	29.000	2.400	194.000	325.000
T4DB 150	150.000	210.000	32.000	3.050	233.000	390.000
T5ED 090U4	90.000	150.000	42.000	3.000		
T7FC 045/HN3Q	45.000	95.000	29.000	0.920		
T7FC 050	50.000	105.000	32.000	1.200		
T7FC 055	55.000	115.000	34.000	1.600		
T7FC 060	60.000	125.000	37.000	2.050		
T7FC 065	65.000	130.000	37.000	2.200		
T7FC 070	70.000	140.000	39.000	2.650		
T7FC 075	75.000	150.000	42.000	3.250		
T7FC 080	80.000	160.000	45.000	3.950		
T7FC 095/CL-7CVQ051	95.000	180.000	49.000	5.250	275.000	400.000